

Micrometer Adjustable - Automatic Reset Torque Wrenches

Micrometer Adjustable "Automatic Reset" Torque Wrenches feature a distinct breaking action when the set torque is reached. The breaking action is greatest at the upper level of the scale where there is more pressure on the spring. Once the pressure is released, the wrench will automatically reset itself, ready to operate again.

Features:

- Left and right hand operation
- Ratchet Head
- English & Metric scales
- Positive Lock with Spring Loaded pull down Lock Ring
- Super rugged knurled metal handle for industrial use
- Socket Locking Device
- Durable
- Accuracy +/- 4% both directions
- Meets or exceeds Australian Standards



Part No.	Torque Range (English)	Graduation (English)	Torque Range (Metric)	Graduation (Metric)	Square Drive	Head Style	Length cm	Packed Weight kg.
370000	30-200in.lbs	1in.lbs	3.9-22.0Nm	1.1dNm	3/8"	Ratchet	25	.61
370000B	30-200in.lbs	1in.lbs	3.9-22.0Nm	1.1dNm	1/4"	Ratchet	25	.61
370050	10-50in.lbs	0.5in.lbs	14-54dNm	1.1dNm	1/4"	Ratchet	25	.61
371000	5-75ft.lbs	0.5ft.lbs	10.2-98.3Nm	0.7Nm	3/8"	Ratchet	39	1.41
371080	10-80ft.lbs	0.5ft.lbs	16.9-105.1Nm	0.7Nm	3/8"	Ratchet	39	1.49
371100	10-100ft.lbs	0.5ft.lbs	16.9-132.2Nm	0.7Nm	3/8"	Ratchet	39	1.41
372000	20-150ft.lbs	1ft.lbs	34-197Nm	1.5Nm	1/2"	Ratchet	47	1.81
373000	30-200ft.lbs	1ft.lbs	47-264Nm	1.5Nm	1/2"	Ratchet	47	1.83
374000	30-250ft.lbs	1ft.lbs	47-332Nm	1.5Nm	1/2"	Ratchet	54	1.95
375000	80-400ft.lbs	5ft.lbs	108-540Nm	7Nm	3/4"	Ratchet	81	5.93
376000	100-600ft.lbs	5ft.lbs	135-779Nm	7Nm	3/4"	Ratchet	109	7.26
377000	200-1000ft.lbs	5ft.lbs	305-1320Nm	7Nm	1"	Ratchet	178	18.62

Note: Part No. 371080 has a ratcheting Flex Head that pivots 15 degrees in both directions.

Detachable Head Torque Wrenches

As part of the 37 Series of torque wrenches Warren and Brown have introduced detachable head versions of the 376000 and 377000 heavy duty wrenches. Utilising these wrenches allows a variety of combinations of open end and 12 point ring attachments up to 1000ft.lbs/1320Nm.

Part No.	Torque Range (ft.lbs)	Grad	Torque Range (Nm)	Grad Metric	Length	Packed Weight kg.
376000DET	100-600ft.lbs	5ft.lbs	135-779 Nm	7Nm	109	6
377000DET	200-1000 ft.lbs	5ft.lbs	305-1320 Nm	7Nm	179	15



Attachments are made to order. Almost any special attachment can be produced.